

Document number : pe82.00-p-2700-99|a
Document title : Wiring diagram of D2 bus

Code:	Designation:	Position:
A2	Radio	3 A
A2/13	Sound amplifier	3 L
A2/6	CD player with changer	12 A
A2/6	CD player with changer	20 A
A34/4	Telephone interface	9 L
A35/17	D2B telephone and TELE AID transmitter/receiver	18 L
A35/8	Telephone transmitter/receiver	13 L
A35/8	Telephone transmitter/receiver	18 L
N123/1	Universal Portable CTEL Interface (UPCI [UHI]) control unit	24 L
U1	Valid for USA	7 H
U1	Valid for USA	11 J
U1	Valid for USA	11 J
U2	Valid for all exceptUSA	21 J
U2	Valid for all exceptUSA	21 J
U2	Valid for all exceptUSA	22 G
U2	Valid for all exceptUSA	22 G
U2	Valid for all exceptUSA	23 J
U2	Valid for all exceptUSA	23 J
U20	Valid for all (except USA Japan)	16 H
U200	Valid for TELE AID	16 H
U200	Valid for TELE AID	16 H
U52	Valid for Japan	16 H
U801	Valid for UHI (Universal Portable CTEL Interface)	22 H
X30/14	Wake-up signal/diagnosis distributor connector	6 L
X99/9	Separation point 9	7 F



